



Towards Optimal Snow Information from Space: A Synthetic Comparison of Observation Constellation Configurations

Prof. Bart Forman (PI, University of Maryland)

Dr. Sujay Kumar (Co-I, NASA GSFC)

Jonathan P. Verville (Co-I, NASA GSFC)

Dr. Sreeja Nag (Co-I, NASA Ames)

Joseph E. Gurganus (NASA GSFC)

Lizhao Wang (University of Maryland)

Jongmin Park (University of Maryland)

Jawairia Ahmad (University of Maryland)

Earth Science Technology Forum NASA Ames, Mountain View, CA June 11-13, 2019







Importance of Snow



- Snow is a **significant contributor** to terrestrial freshwater supply
 - Up to 80% of runoff in some Western states
- Vital resource for >1 billion people worldwide
 - Not exactly sure how much snow is out there
 - Difficult to measure; significant uncertainty;
- Global warming → rising snow line
 - reduced virtual reservoir; accelerated hydrologic cycle;









NASA Decadal Survey



- Global warming → rising snow line → reduced virtual reservoir
- Goal is to improve snow mass estimation at regional / continental scales
 - No dedicated snow mission
 - Water security → food+energy security → national security

TABLE S.1 Science and Applications Priorities for the Decade 2017-2027


Science and Applications Area	Science and Applications Questions Addressed by MOST IMPORTANT Objectives		
Coupling of the Water and Energy Cycles	 (H-1) How is the water cycle changing? Are changes in evapotranspiration and precipitation accelerating, with greater rates of evapotranspiration and thereby precipitation, and how are these changes expressed in the space-time distribution of rainfall, snowfall, evapotranspiration, and the frequency and magnitude of extremes such as droughts and floods? (H-2) How do anthropogenic changes in climate, land use, water use, and water storage interact and modify the water and energy cycles locally, regionally and globally and what are the short- and long-term consequences? 		





Satellite-derived Snow "Information"










Multi-dimensional Trade Space





= Passive Microwave Radiometer

= Synthetic Aperture RADAR


= Optical LiDAR






Trade-off Space: Coverage vs. Resolution







- Explore **trade-off** between engineering and science
 - Field-of-View (FOV)?
 - Platform altitude?
 - Repeat cycle?
 - Single platform vs. constellation?
 - Orbital configuration(s)?
- Tradespace Analysis Tool for Constellations (TAT-C)
 - *Le Moigne et al. [2016]*
- How do we get the most scientific bang for our buck?





Trade-off Space: Swath Width vs. Coverage



Wide Swath LiDAR

C-band SAR


Sensor	1-day (Snow / Land+Ocean)	3-day (Snow / Land+Ocean)	30-day (Snow / Land+Ocean)
Wide Swath LiDAR	5.4% / 3.9%	15% / 11%	55% / 55%
C-band SAR	40% / 28%	79% / 65%	96% / 91%
Passive MW Radiometer	98% / 89%	>99% / 99%	>99% / 99%





Geophysical to Observational Space










NASA Land Information System (LIS)



- Models land surface processes (including snow)
- Integrates satellite-based observational data products with land surface modeling and data assimilation techniques



Kumar et al. (2006), Land Information System: An interoperable framework for high resolution land surface modeling, Environmental Modeling and Software





Research Objectives



Science and mission planning questions


- 1) What observational records are needed (in space and time) to maximize terrestrial snow experimental utility?
- 2) How might observations be coordinated (in space and time) to maximize this utility?
- 3) What is the additional utility associated with an additional observation?
- 4) How can future mission costs be minimized while ensuring Science requirements are fulfilled?





Observing System Simulation Experiment (OSSE)










Synthetic Snow Depth Retrieval Results









Research Summary



- Global snow mission will require evidence of achievable science via OSSE . . . or some other means
- NASA LIS provides "nature run" plus assimilation framework
- TAT-C provides spatiotemporal sub-sampling of observations, including cost estimates and risk assessments
- Machine learning maps model state(s) into observation space (i.e., T_b and σ_0)
- Snow **OSSE** is on-going . . . production runs in process.







Thank You!

Questions and/or comments?





Extra Slides








Spatiotemporal Variability







SVM Mathematical Framework (1 of 2)



For parameters C>0 and $\varepsilon>0$, the **standard (primal)** form is:

$$\begin{aligned} & \underset{\mathbf{w}, \ \delta, \ \boldsymbol{\xi}, \ \boldsymbol{\xi}^*}{\text{minimize}} & & \frac{1}{2} \langle \mathbf{w} \cdot \mathbf{w} \rangle + C \sum_{i=1}^m \left(\xi_i + \xi_i^* \right) \\ & \text{subject to} & & \langle \mathbf{w} \cdot \phi(\mathbf{x}_i) \rangle + \delta - z_i \leq \varepsilon + \xi_i \\ & & z_i - \langle \mathbf{w} \cdot \phi(\mathbf{x}_i) \rangle - \delta \leq \varepsilon + \xi_i^* \\ & & \xi_i, \xi_i^* \geq 0, i = 1, 2, \dots, m. \end{aligned}$$

where m is the available number of T_b measurements in time (for a given location in space), z_i is a T_b measurement at time i, and ξ and ξ^* are slack variables.





SVM Mathematical Framework (2 of 2)



Primal optimization is commonly solved in **dual form** as:

$$\begin{split} & \underset{\alpha_i, \ \alpha_i^*}{\text{minimize}} & \quad \frac{1}{2} \sum_{i,j=1}^m \left(\alpha_i - \alpha_i^*\right) \left(\alpha_j - \alpha_j^*\right) \left\langle \phi(\mathbf{x}_i) \cdot \phi(\mathbf{x}_j) \right\rangle \\ & \quad + \varepsilon \sum_{i=1}^m \left(\alpha_i + \alpha_i^*\right) - \sum_{i=1}^m z_i \left(\alpha_i - \alpha_i^*\right) \\ & \quad \text{subject to} & \quad \sum_{i=1}^m \left(\alpha_i - \alpha_i^*\right) = 0, \\ & \quad \alpha_i \ , \ \alpha_i^* \in [0 \ , \ C] \ , \ i = 1, 2, \dots, m \end{split}$$

where α_i and α_i^* are Lagrangian multipliers, $\langle \phi(\mathbf{x}_i) \cdot \phi(\mathbf{x}_j) \rangle$ is the inner dot product of $\phi(\mathbf{x}_i)$ and $\phi(\mathbf{x}_j)$, ε is the specified error tolerance, and C is a positive constant that dictates a penalized loss during training.





Blank Slide

